



LS

Overhead Stirrers

Overhead stirrer with 40 Ncm torque
for low-medium viscosity application



Resistant and Easy-to-Use

The LS is an intuitive overhead stirrer ensuring safety with overload, over-current and overheating protection.

- Maximum torque of 40 Ncm
- Supports applications with a maximum viscosity of 25 000 mPa*s
- Electronic speed regulation from 50 to 2000 rpm, up to 25 L
- Long life, robust motor
- Easy-chuck to change the shafts without tools
- Automatically stops if blocked – no burn-out or damage
- Overload, overcurrent and overtemperature protection
- Sealed to IP 40 standard



INSTRUMENT - CODE

LS	110-230 V / 50-60 Hz	F201A0151
LS - System*	110-230 V / 50-60 Hz	SA201A0151

* Included in the system: LS Overhead Stirrer, Universal H-Stand, Double Clamp and Stirring Shaft with Fixed Blade

TECHNICAL DATA

CONSTRUCTION MATERIAL	Technopolymer and epoxy painted aluminum alloy
CHUCK RANGE	1 - 10 mm
ELECTRONIC PROTECTION RATING CEI EN 60529	IP 40
ELECTRONIC SPEED REGULATION	From 50 to 2000 rpm
STIRRING VOLUME MAX (H2O)	Up to 25 L
MAX VISCOSITY	25000 (mPa*s)*
TORQUE MAX	40 Ncm
ALLOWED ROOM TEMPERATURE	From 0 to 40 °C
DIMENSION (WXHXD)	80x215x196 mm (3.1x8.5x7.7 in)
POWER	120 W
WEIGHT	2.3 Kg (5.0 lb)



VELP Official Partner

We reserve the right to make technical alterations
We do not assume liability for errors in printing, typing or transmission

DESIGNED AND MANUFACTURED IN ITALY



ITALY - HQ
Via Stazione 16
20865 Usmate (MB) Italy
Tel. +39 039 628811
velpitalia@velp.com

INDIA
velpindia@velp.com

USA
155 Keyland Court, Bohemia
NY 11716 - U.S.
Tel. +1 631 573 6002
velpusa@velp.com

CHINA
Xinlong Rd Building 28, Lane 1333
Shanghai city - China
Tel. +86 180 1755 7329
velpchina@velp.com