



FTC 120

Cooled Incubator

Designed for BOD incubation



High efficiency with A+ energy rate

- Usable volume 190 L
- Auto-Tuning thermoregulation system ensures optimum thermal homogeneity and stability ($\pm 0,5^{\circ}\text{C}$)
- Constant temperature 20 °C
- Cooling system in A+ class energy rate
- MODBUS communication protocol
- Internal sockets to power devices
- Intuitive digital interface
- Accepts 3 BOD Sensor System 6, or 2 BOD Sensor System 10
- Accepts 3 RESPIROMETRIC Sensor System 6



INSTRUMENT - CODE

FTC 120

230V/50-60Hz

F10300305



TECHNICAL DATA

DIGITAL DISPLAY	2-digit, 1 °C resolution
USABLE INTERNAL VOLUME	109 liters
ELECTRONIC THERMOREGULATION SYSTEM	Traditional
TEMPERATURE REGULATION	20 °C constant
INTERNAL TEMPERATURE STABILITY	$\pm 0.5^{\circ}\text{C}$
INTERNAL TEMPERATURE HOMOGENEITY	$\pm 0.5^{\circ}\text{C}$
NUMBER OF SHELVES INCLUDED	2
NUMBER OF INTERNAL SOCKETS	2
POWER	120 W
POWER SUPPLY	230 V / 50-60 Hz
WEIGHT	36 kg (79.4 lb)
DIMENSIONS (WXHxD)	540x912x550 mm (21.3x35.9x21.7 in)



We reserve the right to make technical alterations
We do not assume liability for errors in printing, typing or transmission

VELP Official Partner

DESIGNED AND MANUFACTURED IN ITALY



ITALY - HQ
Via Stazione 16
20865 Usmate (MB) Italy
Tel. +39 039 628811
velpitalia@velp.com

INDIA
velpindia@velp.com

USA
155 Keyland Court, Bohemia
NY 11716 - U.S.
Tel. +1 631 573 6002
velpusa@velp.com

CHINA
Xinlong Rd Building 28, Lane 1333
Shanghai city - China
Tel. +86 18017557329
velpchina@velp.com